

BEAUNE S Kombi



wood or pellet without electricity

Technical specifications of the combo stove:

measurements (cm)	width	hei	ght	depth
stove	44	12	28	44
combustion chamber	26	4	8	30
fire glass	33	46		
fire door	39	58		
flue pipe connection f	Ø 15 to↑			
height to pipe socket above				129,5
outside air connectio	n Ø 10 to → or ↓			
height to mid connection horizontal			7,5	
depth to mid connection	d connection vertical		17,5	
total weight	chamotte br	icks	heat accumulator	
135 kg	15 kg	15 kg		-
data for	pellet bo	x	wood	
nominal heat output	5,4 kW		5,8 kW	
output range	5,4 kW		5,8 - 3 kW	
efficiency	86%		84%	
heating capability*	70 - 180 m³		70 - 210 m³	
amount of fuel	2,2 kg		1,8 kg / h	
fire duration	up to 1,5 h		up to 1,5 h	
heat release	up to 2,5 h		up to 2,5 h	
flue gas flow volume	6,2 g/s		5,28 g/s	
exhaust °C (nozzle)	226 °C		255 °C	
min/max feed press.	12 / 15 Pa		12 / 15 Pa	
CO (13%/O2) [mg/m³]	456,7		1208	
CO (13%/O2) [%]	0,037		0,097	
dust (13%/O2) [mg/m ³	29,1		27,3	
NOx (13%/02) [mg/m ³]	76		129	
CxHy (13%/O2) [mg/m³]	3,5		34,8	
wall distance, rear	15 cm		15 cm	
wall distance, side	15 cm		15 cm	
distance to the front	80 cm		80 cm	

Fulfils the latest standards in burning wood, wood-briquettes and pellets (please see appliacable standards).

Please check the instruction manual for this wood & pellet burning stove.


Suitable for multiple chimneys.


* depending on stove location in the living area, room isolation, height of the room and amount of fuel

Subject to alterations; errors including printer's errors.

Our specialised stove builders and retailers will assist you with practical advice.







Technical specifications of the small round wood-stove, model Beaune S Kombi

ENR	model	delivery time			
245-2001	Beaune S Kombi ↑ fixed	3			
	 wood only (without pellet accessories) 				
	 stove body and door in steel anthracite 				
	steel lid anthracite				
	fire chamber rear wall				
	made of 3 cm heat-storing chamotte				
	 self-locking door with cool door handle 				
245-2021	Beaune S Kombi ↑ rotatable	3			
	 wood only (without pellet accessories) 				
	stove body and door in steel anthracite				
	store body and door in steel antinacite steel lid anthracite				
	fire chamber rear wall				
	made of 3 cm heat-storing chamotte				
	 self-locking door with cool door handle 				
	pellet accessories for the small round	combi stove			
558-2001	-				
556-2001	pellet box with 5,4 kW (at purchase with a stove)				
	pellet box with 5,4 kW (retrofit kit)				
	made of heat-resistant stainless steel				
	with 3 black ceramic special glasses				
	 comes with lighter, silicone gloves, pellet-felt bag up to 20 kg, cleaning brushes, pellet shovel provided 				
	cleaning brushes, pener shover provided				
	accessories for the round stove	ł			
29 232 311	floor protector stainless steel (see accessories)				
29 232 400	floor protector glass (see accessories)				
	especially for this stove type				
	Outside air connection is prepared:				
	Be sure to specify when ordering:				
	outside air connection horizontal or vertical				
	(is included in scope of delivery - rotatable only vertical possible)				
	For other connection accessories, please see list of accessories.				
	special features of the small round sto				
	•				
	The Beaune S Kombi is easy to operate in both cases, with wood or with pellet				
	with wood or with pellet. Pellet-wood-fire accessories, heating with 2 kinds of fire, independent & without electricity.				
	The small round combi stove Beaune S Kombi				
	its slim diameter of 44 cm allows a discreet setup				
	saving room and still getting an excellent performance				
	fits in almost every interior room arrangements				
	a pellet box can be requested to make the stove even more economic				
	both wood and pellet fire will give you the pleasure of fire romantic the pollet fire is just as romantic as the wood fire				
	the pellet fire is just as romantic as the wood fire the maintifue the bast distribution because throughout radiant bast				
	the majority of the heat distribution happens throughout radiant heat				
	easy to swap between wood and pellet within o	-			
	• when using pellet only, the ash tray needs to be				
	(when the instructions for pellet burning are bein	- ,			
	choose your glass or stainless steel floor protect	ctor from the list of accessories			
	easy to remove during summer times				