

NIMES Steel / Crystal / Stone

wood or pellet without electricity

Technical specifications of the round stove NIMES:

combustion chamber 34 60 30 fire glass 36 48 fire door 44 60 flue pipe connection Ø 15 to 110height to pipe socket above $109,5$ outside air connection norizontal 10 depth to mid connection vertical $25 / 27$ total weightchamotte bricks148 / 167 / 284 kg $22 kg$ data forpellet boxnominal heat output $5,0 kW$ output range $5 - 3 kW$ efficiency 76% heating capability* $50 - 150 m^3$ amount of fuel $2,7 kg$ fire durationup to 2 hup to 6 hup to 8 hflue gas flow volume $8,28 g/s$ exhaust °C (nozzle) $270 °C$ min/max feed press. $12 / 15 Pa$ CO (13%/O2) [mg/m³] $226,9$ Rox (13%/O2) [mg/m³] 17 52 34 NOx (13%/O2) [mg/m³] 17 sull distance, rear $10 cm$	reonnould opeoinould				
Combustion chamber fire glass 34 36 60 30 fire door 34 44 60 flue pipe connection Ø 15 to \uparrow height to pipe socket above $109,5$ outside air connection Ø 10 to \rightarrow or \downarrow height to mid connection horizontal depth to mid connection vertical 10 $25 / 27$ total weightchamotte bricksheat accumulator $148 / 167 / 284$ kg 22 kg 28 kgdata for nominal heat output $5,0$ kW $4,7 / 5,1^{**}$ kWoutput range $5 - 3$ kW $5,6 - 3$ kWefficiency fire duration 76% up to 2 h up to 4 h $75 / 81^{**} \%$ heat releaseup to 6 hup to 8 hflue gas flow volume min/max feed press. $8,28$ g/s $226,9$ $300 / 235^{**} °C$ CO (13%/O2) [mg/m³] OU (13%/O2) [mg/m³] 17 12 34 NOX (13%/O2) [mg/m³] wall distance, rear 10 cm 00 cm	measurements (cm)	width	hei	ght	depth
fire glass fire door36 4448 60flue pipe connection Ø 15 to ↑ height to pipe socket above109,5outside air connection Ø 10 to → or ↓ height to mid connection horizontal depth to mid connection vertical10 25 / 27total weightchamotte bricksheat accumulator148 / 167 / 284 kg22 kg28 kgdata forpellet boxwoodnominal heat output output range5,0 kW4,7 / 5,1** kWoutput range5,- 3 kW5,6 - 3 kWefficiency76%75 / 81** %heating capability*50 - 150 m³70 - 210 m³amount of fuel fire duration2,7 kg1,7 kg / hflue gas flow volume exhaust °C (nozzle)270 °C300 / 235** °Cmin/max feed press.12 / 15 Pa12 / 15 PaCO (13%/O2) [mg/m³] (13%/O2) [mg/m³]226,9887 (0,071OX (13%/O2) [mg/m³]125133 (2 KHy (13%/O2) [mg/m³]1752wall distance, rear10 cm10 cm	stove	51,5/51,5/55,5	123/12	23/125	51,5/51,5/55,5
fire door4460flue pipe connection Ø 15 to ↑ height to pipe socket above109,5outside air connection Ø 10 to → or ↓ height to mid connection horizontal depth to mid connection vertical10depth to mid connection vertical25 / 27total weightchamotte bricksheat accumulator148 / 167 / 284 kg22 kg28 kgdata forpellet boxwoodnominal heat output5,0 kW4,7 / 5,1** kWoutput range5 - 3 kW5,6 - 3 kWefficiency76%75 / 81** %heating capability*50 - 150 m³70 - 210 m³amount of fuel2,7 kg1,7 kg / hfire durationup to 2 hup to 4 hheat releaseup to 6 hup to 8 hflue gas flow volume8,28 g/s5,89 g/sexhaust °C (nozzle)270 °C300 / 235** °Cmin/max feed press.12 / 15 Pa12 / 15 PaCO (13%/O2) [mg/m³]226,9887CO (13%/O2) [mg/m³]125133CXHy (13%/O2) [mg/m³]1752wall distance, rear10 cm10 cm	combustion chamber	34	6	0	30
flue pipe connection Ø 15 to \uparrow height to pipe socket above109,5outside air connection Ø 10 to \rightarrow or \downarrow height to mid connection vertical10depth to mid connection vertical25 / 27total weightchamotte bricksheat accumulator148 / 167 / 284 kg22 kg28 kgdata forpellet boxwoodnominal heat output5,0 kW4,7 / 5,1** kWoutput range5 - 3 kW5,6 - 3 kWefficiency76%75 / 81** %heating capability*50 - 150 m³70 - 210 m³amount of fuel2,7 kg1,7 kg / hfire durationup to 2 hup to 4 hheat releaseup to 6 hup to 8 hflue gas flow volume8,28 g/s5,89 g/sexhaust °C (nozzle)270 °C300 / 235** °Cmin/max feed press.12 / 15 Pa12 / 15 PaCO (13%/O2) [mg/m³]226,9887CO (13%/O2) [mg/m³]125133CXHy (13%/O2) [mg/m³]1752wall distance, rear10 cm10 cm	fire glass	36	4	8	
height to pipe socket above109,5outside air connection \emptyset 10 to \rightarrow or 1height to mid connection horizontal10depth to mid connection vertical25 / 27total weightchamotte bricks148 / 167 / 284 kg22 kg28 kgdata forpellet boxnominal heat output5,0 kWoutput range5 - 3 kWefficiency76%75 / 81** %heating capability*50 - 150 m³amount of fuel2,7 kgfire durationup to 2 hup to 6 hup to 4 hheat release270 °Cmin/max feed press.12 / 15 PaCO (13%/O2) [mg/m³]226,9CO (13%/O2) [mg/m³]226,9RCO (13%/O2) [mg/m³]125MOX (13%/O2) [mg/m³]125133133CxHy (13%/O2) [mg/m³]1752wall distance, rear10 cm10 cm	fire door	44	6	0	
height to pipe socket above109,5outside air connection \emptyset 10 to \rightarrow or \downarrow 10height to mid connection horizontal10depth to mid connection vertical25 / 27total weightchamotte bricks148 / 167 / 284 kg22 kg28 kgdata forpellet boxnominal heat output5,0 kWoutput range5 - 3 kWefficiency76%75 / 81** %heating capability*50 - 150 m³amount of fuel2,7 kgfire durationup to 2 hup to 6 hup to 8 hflue gas flow volume8,28 g/sexhaust °C (nozzle)270 °C300 / 235** °Cmin/max feed press.12 / 15 PaCO (13%/O2) [mg/m³]226,9RC (13%/O2) [mg/m³]125133133CxHy (13%/O2) [mg/m³]1752wall distance, rear10 cm10 cm	flue pipe connection (Ø 15 to †			
outside air connection		••			109.5
height to mid connection horizontal depth to mid connection vertical10 $25 / 27$ total weightchamotte bricksheat accumulator148 / 167 / 284 kg22 kg28 kgdata forpellet boxwoodnominal heat output5,0 kW4,7 / 5,1** kWoutput range5 - 3 kW5,6 - 3 kWefficiency76%75 / 81** %heating capability*50 - 150 m³70 - 210 m³amount of fuel2,7 kg1,7 kg / hfire durationup to 2 hup to 4 hheat releaseup to 6 hup to 8 hflue gas flow volume8,28 g/s5,89 g/sexhaust °C (nozzle)270 °C300 / 235** °Cmin/max feed press.12 / 15 Pa12 / 15 PaCO (13%/O2) [mg/m³]226,9887CO (13%/O2) [mg/m³]125133CXHy (13%/O2) [mg/m³]1752wall distance, rear10 cm10 cm					,.
depth to mid connection vertical 25 / 27 total weight chamotte bricks heat accumulator 148 / 167 / 284 kg 22 kg 28 kg data for pellet box wood nominal heat output 5,0 kW 4,7 / 5,1** kW output range 5 - 3 kW 5,6 - 3 kW efficiency 76% 75 / 81** % heating capability* 50 - 150 m³ 70 - 210 m³ amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 125 133 CXHy (13%/O2) [mg/m³] 125 133 NOx (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	outside air connection	n Ø 10 to → or ↓			
total weight chamotte bricks heat accumulator 148 / 167 / 284 kg 22 kg 28 kg data for pellet box wood nominal heat output output range 5,0 kW 4,7 / 5,1** kW output range 5 - 3 kW 5,6 - 3 kW efficiency 76% 75 / 81** % heating capability* 50 - 150 m³ 70 - 210 m³ amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 125 133 CN (13%/O2) [mg/m³] 125 133 NOX (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	height to mid connecti				
148 / 167 / 284 kg 22 kg 28 kg data for pellet box wood nominal heat output output range 5,0 kW 4,7 / 5,1** kW output range 5 - 3 kW 5,6 - 3 kW efficiency 76% 75 / 81** % heating capability* 50 - 150 m³ 70 - 210 m³ amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 125 133 CN (13%/O2) [mg/m³] 125 133 CXHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm					25 / 27
data for pellet box wood nominal heat output 5,0 kW 4,7 / 5,1** kW output range 5 - 3 kW 5,6 - 3 kW efficiency 76% 75 / 81** % heating capability* 50 - 150 m³ 70 - 210 m³ amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 125 133 CXHy (13%/O2) [mg/m³] 125 133 CXHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	v	chamotte br	icks	hea	t accumulator
nominal heat output 5,0 kW 4,7 / 5,1** kW output range 5 - 3 kW 5,6 - 3 kW efficiency 76% 75 / 81** % heating capability* 50 - 150 m³ 70 - 210 m³ amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 125 133 NOx (13%/O2) [mg/m³] 125 133 CxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	_	-			28 kg
output range 5 - 3 kW 5,6 - 3 kW efficiency 76% 75 / 81** % heating capability* 50 - 150 m³ 70 - 210 m³ amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 12 34 NOx (13%/O2) [mg/m³] 125 133 cxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm			K (
efficiency 76% 75 / 81** % heating capability* 50 - 150 m³ 70 - 210 m³ amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 12 34 NOx (13%/O2) [mg/m³] 125 133 CxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm					
heating capability* 50 - 150 m³ 70 - 210 m³ amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 12 34 NOx (13%/O2) [mg/m³] 125 133 CXHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	output range		'		<i>,</i>
amount of fuel 2,7 kg 1,7 kg / h fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [mg/m³] 0,018 0,071 dust (13%/O2) [mg/m³] 125 133 CXHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm				7	75 / 81** %
fire duration up to 2 h up to 4 h heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [%] 0,018 0,071 dust (13%/O2) [mg/m³] 125 133 NOx (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	heating capability*	50 - 150 r	n³	7	70 - 210 m³
heat release up to 6 h up to 8 h flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [%] 0,018 0,071 dust (13%/O2) [mg/m³] 125 133 CXHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	amount of fuel	2,7 kg			1,7 kg / h
flue gas flow volume 8,28 g/s 5,89 g/s exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [%] 0,018 0,071 dust (13%/O2) [mg/m³] 12 34 NOx (13%/O2) [mg/m³] 125 133 CxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	fire duration	up to 2 h	า		up to 4 h
exhaust °C (nozzle) 270 °C 300 / 235** °C min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [%] 0,018 0,071 dust (13%/O2) [mg/m³] 12 34 NOx (13%/O2) [mg/m³] 125 133 cxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	heat release	up to 6 h	ı		up to 8 h
min/max feed press. 12 / 15 Pa 12 / 15 Pa CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [%] 0,018 0,071 dust (13%/O2) [mg/m³] 12 34 NOx (13%/O2) [mg/m³] 125 133 CxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	flue gas flow volume	8,28 g/s		5,89 g/s	
CO (13%/O2) [mg/m³] 226,9 887 CO (13%/O2) [%] 0,018 0,071 dust (13%/O2) [mg/m³] 12 34 NOx (13%/O2) [mg/m³] 125 133 CxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	exhaust °C (nozzle)	270 °C		30	0 / 235** °C
CO (13%/O2) [%] 0,018 0,071 dust (13%/O2) [mg/mi 12 34 NOx (13%/O2) [mg/mi] 125 133 CxHy (13%/O2) [mg/mi] 17 52 wall distance, rear 10 cm 10 cm	min/max feed press.	12 / 15 P	а		12 / 15 Pa
dust (13%/O2) [mg/m³ 12 34 NOx (13%/O2) [mg/m³] 125 133 CxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	CO (13%/O2) [mg/m ³]	226,9			887
NOx (13%/O2) [mg/m³] 125 133 CxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	CO (13%/O2) [%]	0,018			0,071
CxHy (13%/O2) [mg/m³] 17 52 wall distance, rear 10 cm 10 cm	dust (13%/O2) [mg/m	12			34
wall distance, rear 10 cm 10 cm	NOx (13%/02) [mg/m ³]	125			133
	CxHy (13%/O2) [mg/m ³]	17			52
	wall distance, rear	10 cm			10 cm
	wall distance, side	10 cm			10 cm
distance to the front 65 cm 90 cm	distance to the front	65 cm		90 cm	

Fulfils the latest standards in burning wood, wood-briquettes and pellets (please see appliacable standards).

Please check the instruction manual for this wood & pellet burning stove.

Suitable for multiple chimneys.


Optionally with balanced flue operation DIBt-Approval Z-43.12-354.


- * depending on stove location in the living area, room isolation, height of the room and amount of fuel
- ** emission values at 75 cm flue pipe length

Subject to alterations; errors including printer's errors.

Our specialised stove builders and retailers will assist you with practical advice.







Round stove, model Nimes

ENR	model	delivery time			
234-2201	Nimes Steel ↑ 3				
	 stove body steel anthracite 				
	 fire door and top cover in black 				
232-2101	Nimes Crystal ↑	3			
202-2101	stove body crystal glass in shiny black	5			
	 fire door and top cover in black 				
232-2201	Nimes Crystal ↑	3			
232-2201	-	5			
	stove body crystal glass white matted				
000.0004	fire door and top cover in black				
233-2201	Nimes Stone ↑	3			
	stove body stone light grey blasted				
	fire door, cornice and top cover in black				
233-2401	Nimes Stone ↑	3			
	stove body stone cream smooth				
	 fire door, cornice and top cover in black 				
233-2101	Nimes Stone ↑	3			
	 stove body stone cream chiselled 				
	 fire door, cornice and top cover in black 				
233-2501	Nimes Stone ↑	3			
	 stove body stone anthracite flamed 				
	 fire door, cornice and top cover in black 				
	pellet accessories for the round stove				
554-2004	pellet box with 5 kW (at purchase with a stove)				
	pellet box with 5 kW (retrofit kit)				
	made of heat-resistant stainless steel				
	• with 1 black cream special glass				
	• with lighter, silicone gloves, pellet-felt bag up to 20 l	kg,			
	cleaning brushes, pellet shovel provided				
	additional heat accumulator (4 stones with 28 kg)				
303 002	DIBt-approval for air-independent versions.				
	(not possible for rotatable versions)				
	on request with stone lid in either: - natural stone light grey blasted - natural stone chiselled grey - natural stone anthracite flamed				
	base for rotatable version				
	(only with vertical outside air connection possible!)	/ertical outside air connection possible!)			
29 232 311	floor protector stainless steel (see accessories)				
29 232 400	floor protector glass (see accessories)				
	Be sure to specify when ordering: outside air connection horizontal or vertical				
	special features of the round stove, mod				
	Heat without electrical power and use all advantage	·			
	Swap easy and comfortable between fuels within 5	minutes.			
	 Discover the special features of our fire-combo-romantic on YouTube. 				
	Free to choose the fuel makes you more independent.				
	Get whatever is cheapest at the moment and save money.				
	The round stove, model Nimes				
	Fire logs create a special and very interesting flame and even a fire-romantic.				
	• the ideal model for a corner, only 10 cm wall distance needed				
	• circular rear wall offers ideal views				
	beautiful natural stone surfaces				
	soft body without overlapping edges				
	comfortable and always cool - the stainless steel door handle				
	patented, easy to use and self-closing door latch				
	all editions are available with additional heat accumulator				
also available as a rotatable edition					
	Please also look up the features o	of the natural stone collection!			
	ו ופמשם מושט וטטה עף נוום ובמנעופש נ				