

ODIN BF

wood or pellet without electricity

Technical specifications of the stove with roast & bake comp.:

			•
measurements (cm)	width	height	depth
stove	64	155	63
combustion chamber	34	31	35
fire glass	34	49	
fire door	45	60	
roast & bake comp.	34	30	45
flue pipe connection height to mid pipe rea	134		
height to pipe socket a	154		
outside air connection			
height to mid connecti	23,5		
depth to mid connection	16		

aoptii to iiiia comiootii	on vortious		
total weight	chamotte bricks	heat accumulator	
457 kg	60 kg	-	
data for	pellet box	wood	
nominal heat output	8,7 kW	7,5 kW	
output range	8,7 - 6,7 kW	8,2 - 4,6 kW	
efficiency	83%	87%	
heating capability*	70 - 350 m³	70 - 350 m³	
amount of fuel	7,5 kg	2,2 kg / h	
fire duration	up to 5 h	up to 5 h	
heat release	up to 18 h	up to 18 h	
flue gas flow volume	9,71 g/s	6,8 g/s	
exhaust °C (nozzle)	280 °C	211°C	
min/max feed press.	12 / 15 Pa	12 / 15 Pa	
CO (13%/O2) [mg/m³]	1073	806	
CO (13%/O2) [%]	0,086	0,065	
dust (13%/O2) [mg/m ³	22	32	
NOx (13%/O2) [mg/m³]	73	116	
CxHy (13%/O2) [mg/m³]	64	27	
wall distance, rear	15 cm	15 cm	
wall distance, side	15 cm	15 cm	
distance to the front	100 cm	100 cm	

Fulfils the latest standards in burning wood, wood-briquettes and pellets (please see appliacable standards).


Please check the instruction manual for this wood & pellet burning stove.


Suitable for multiple chimneys.


* depending on stove location in the living area, room isolation, height of the room and amount of fuel

Subject to alterations; errors including printer's errors.

Our specialised stove builders and retailers will assist you with practical advice.







Stove with roasting and baking compartment, model Odin BF

ENR	model	delivery time			
211-2001	Odin BF ↑	4			
211-2002	Odin BF →	4			
	stove body steel anthracite				
	side panels and with natural stone top cover in grey	l hlasted			
211-2003	Odin BF ↑	4			
211-2009	Odin BF →	4			
211-2009		4			
	stove body steel anthracite side people and with natural stans to a sever in second	l am a ma a th			
044 0000	 side panels and with natural stone top cover in crea Odin BF ↑ 				
211-2020		4			
211-2022	Odin BF →	4			
	stove body steel anthracite				
	side panels and lid				
	brushed slate				
	slate nature				
211-2027	Odin BF ↑	4			
211-2030	Odin BF →	4			
	stove body steel anthracite				
	side panels and lid slate, autumn leaves				
	pellet accessories for the stove with roas	ting and baking compar	tment		
551-2004	pellet box with 8,7 kW (at purchase with a stove)				
	pellet box with 8,7 kW (at purchase without stove)				
	 made of heat-resistant stainless steel 				
	 with 3 black ceramic specialised glasses 				
	• with lighter, silicone gloves, pellet-felt bag up to 20 k	kg,			
	cleaning brushes, pellet shovel provided				
29 215 311	floor protector stainless steel (see accessories)				
	included in scope of delivery:				
308 071	tray for roasting and baking compartment				
308 049	chrome grill				
308 075	low-maintenance, anthracite lava rock				
308 057	thermometer for baking compartment				
300 037	thermometer for baking compartment				
	Be sure to specify when ordering:				
	outside air connection horizontal or vertical				
	(is included in scope of delivery)				
	special features of the stove with roasting and baking comp., model Odin BF				
	Heat without electrical power and use all advantages	of this double feature oven: pel	llet and wood!		
	Simple and very easy swap between wood or pellet v	vithin a minute.			
	Discover the special features of our fire-combo-roma	ntic on YouTube.			
	The stove with roast & backing tray, model Odin BF	!			
	baking stove with large heat accumulating through		ny		
	the large backing tray allows cooking above the ron	-	•		
	bake like at granny's times				
		el side walls and two rails for tra	VS		
	 the backing compartment comes with stainless steel side walls and two rails for trays comes with enamelled backing tray, grill and thermometer 				
	comes with enamelied backing tray, grill and thermometer curved doors for the stove and the backing compartment				
	integrated regulator for the smoke extractor				
	Integrated regulator for the Smoke extractor large window for the combustion chamber				
	large combustion chamber for large logs chamatte-stones up to 60mm thick				
	chamotte-stones up to 60mm thick high radiant heat accumulating				
	high radiant heat accumulating adjustable feet for a stable set up				
	adjustable feet for a stable set up				
	 floor protectors made of glass or stainless steel are available at the list of accessories 				
	Please also look up the features of the natural stone collection!				